



PRODUCT DATA SHEET

Anti-Foam

February, 2003

DESCRIPTION

- ◆ **BC-10** is an **anti-foam agent** specially formulated for use in the electronics industry. It contains no silicones, oils or water insoluble compounds that would deposit on sensitive electronic circuit boards and inhibit the adhesion of coatings.
- ◆ **BC-10** is extremely effective, a **small amount of material** (about 10-100cc) will control all the foaming in a 60-gallon spray rinse tank for an entire shift under proper conditions. Avoid adding excess anti foam to the wash sump as once the foaming is under control more material will have little effect.
- ◆ **BC-10** is more effective as the water **temperature increases**. Operating temperatures of 140°F is ideal for the material although it works well even at room temperature.

PHYSICAL PROPERTIES

Appearance	Colorless liquid
Specific gravity	0.951
Flash Point, T.C.C.	140°F

SAFETY **BC-10** is mild skin irritant. Avoid contact with the skin and eyes. Material Safety Data Sheets are available upon request.

PACKAGING **BC-10** anti foam is available in 1-gallon jugs, 5-gallon pails and 55-gallon drums.

STORAGE **BC-10** anti foam has a recommended shelf life of 12 months when stored in the original sealed container at ambient temperatures.

“Our commitment to quality is our most valuable asset”

The information contained herein is offered free of charge for use by technically qualified personnel at their discretion and risk. All information and recommendations contained herein are based on test and data which we believe to be reliable, but the accuracy or completeness is not guaranteed and no warranty of any kind is made with respect hereto.

Manufactured By:
Interflux USA, Inc.
2914 Ladybird Lane
Dallas, TX 75220

Tel: **214-350-5565**
Toll Free: **800-843-3589**
Fax: **214-350-9713**

www.interfluxusa.com